

# Firefighting Truck Control Panel



**Firefighting Truck**



**Firefighting water Pump**



**Electric Hose Reel**



**Electric Fire Monitor**



**Light Tower**



## Product Specifications:

- Pressure manometers  
[Vacuum Pressure Gauge (Diameter 60 mm - range -1~5 bar)]  
[Low Pressure Gauge (Diameter 60 mm - range 0~25 bar)]  
[High Pressure Gauge (Diameter 60 mm - range 0~60 bar)]
- Start & stop switch
- Water tank level indicator
- Warning indicator
- Fuel indicator
- Oil indicator
- Temperature indicator
- Vacuum switch
- High pressure switch
- Low pressure switch
- Gas increase and decrease switches (Pump Speed Control)
- 4 inch full-color graphic LCD
- F4-Series ARM based VL Noise, high reliability processor
- Intelligent algorithm to avoid of dangerous operation
- Using of 3 independent switching regulators
- Operating voltage 12, 24 volts.
- Up to 11 coil drivers (Such as pneumatic valves bobbin, Fans, lights)
- Up to 3 digital RPM sensor inputs
- Up to 5 universal analog input in range [0 – 12 volts or 0-20 mA]
- User friendly setup for selecting device
- Directly contact and switch with **T-Control**

## Additional Options :

- Display Producer Company name
- Foam tank level indicator
- Light tower switch
- Projector switch
- Interior light switch
- PTO switch
- Hose reel switches [Left & Right]
- Monitor switch
- Main valve switch
- Fill tank switch
- Automatic Foam Mixture (AFM) unit

